



<b>IW150A</b>		
<b>Specifications</b>	<b>Values</b>	<b>Notes / Comments</b>
Nominal System Impedance	4 ohm	(Z-min 3.4 ohm)
Frequency Response	80-20K Hz	(average response in room +/- 3 dB)
Frequency Roll Off	80 Hz	(-9 dB 80 Hz near field)
Crossover Frequency	2.0K Hz	"Phase focused" (2nd order)
Tweeter	1 x 1,1" Dome	Coated silk dome / Low compression
Woofer	2 x 5.25"	Coated Glass Fibre
Power Handling	180 watt	Long term IEC-268-5 (cycled input 77-20K Hz)
Power Handling	90 watt	Rated IEC-268-5 (constant input 77-20K Hz)
Recommended Amp Power	25-400 watt	Recommended Amp Power Min / Max
Sensitivity	90 dB	Average SPL 2.83 volt / 1mtr (on axis 200-10K Hz)
Max SPL Continued	110 dB	Sinewave 100-8000 Hz / THD < 10%
Max SPL Peak	116 dB	Sinewave 100-8000 Hz / THD < 10%
System Principle		Sealed enclosure
Connection	Terminal Gold plating	Push terminal 4mm Cable
Finish	Paint	Black cabinet & Front White Grille
Cutout	H x W	13.03 x 11.33 inch / 331 x 288 mm
Cabinet dimensions	H x W	12.95 x 11.25 inch / 329 x 286 mm
Cabinet depth	D	3.74 inch / 95 mm
Dimensions Grille	H x W x D	14.17 x 12.48 inch / 360 x 317 mm
Weight	Netto	21.6 lbs / 9.8 kg

***The Choice of Professionals™***