

IW950		
Specifications.	Values	Notes / Comments.
Nominal system impedance	4 ohm	(Z-min 3.4 ohm)
Frequency response	80-20Khz	(average response in room +/- 3dB)
Frequency roll off	80 Hz	(-9 dB 80 Hz near field)
Crossover frequency	1.6Khz	"Phase focused" (4th / 2nd order)
Tweeter	1 x 1,1" Dome	Coated silk dome / Low compression
Woofers	2 x 5.25"	Coated Glass Fibre
Power handling	180 watt	Long term IEC-268-5 (cycled input 77-20Khz)
Power handling	90 watt	Rated IEC-268-5 (constant input 77-20Khz)
Recommended amp power	25-400 watt	Recommended amp power Min / Max
Sensitivity	90dB	Average SPL 2.83 volt / 1mtr (on axis 200-10KHz)
System principle		Sealed enclosure
Connection	Terminal gold plating	Push terminal 4 mm cable
Finish	Paint	Black cabinet & front / white Grill
Cut out	H x W	18.38 x 8.34 inch / 467 x 212 mm
Cabinet dimensions	H x W	18.30 x 8.26 inch / 465 x 210 mm
Cabinet depth	D	3.74 inch / 95 mm
Dimensions grill	H x W x D	19.52 x 9.44 inch / 496 x 240 mm
Weight	Netto	17.7 lbs / 8 kg
	Version 1. Feb 2019	