

<b>IW95</b>		
<b>Specifications.</b>	<b>Values</b>	<b>Notes / Comments.</b>
Nominal system impedance	4 ohm	(Z-min 3,4 ohm)
Frequency response	80-20Khz	Average response +/- 2dB
Crossover frequency	1.6Khz	"Phase focused" (4th&2nd order)
Tweeter	1.1" Dome	Coated silk dome
Woofers	6.5"	Mineral filled polypropylene
Power handling	140 watt	Long term IEC-268-5 (cycled input 100-20Khz)
Power handling	75 watt	Rated IEC-268-5 (constant input 100-20Khz)
Recommended amp power	25-300 watt	(Recommended amp power to drive speaker)
Sensitivity	91 dB	Average SPL 2.83 Volt / 1mtr (on axis 200-10KHz)
System princip		In wall / Sealed enclosure
Connection	Terminal gold plating	Push terminals
Accessories	Yes	Cut out template / rear foam damping
Installation manual / guide	Yes	
Mounting Depth	D	3.67 inch / 93 mm
Baffle dimensions	H x W	12.16 x 9.13 inch / 309 x 232 mm
Wall cut out	H x W	10.75 x 7.44 inch / 273 x 189 mm
Square Grill dimension	H x W	12.40 x 9.33 inch / 315 x 237 mm
Weight	Netto	10 lbs / 4.6 kg
	Version 1. Feb 2019	