

<b>IW5</b>		
<b>Specifications.</b>	<b>Values</b>	<b>Notes / Comments.</b>
Nominal system impedance	4 ohm	(Z-min 4.9 ohm)
Frequency response	100-20Khz	Average response +/- 2dB
Crossover frequency	1.8Khz	"Phase focused" (4th&2nd order)
Tweeter (shielded)	1" Dome	Coated silk dome / Neodymium magnet
Woofers (shielded)	4"	Polymer coated texture paper
Power handling	80 watt	Long term IEC-268-5 (cycled input 100-20Khz)
Power handling	50 watt	Rated IEC-268-5 (constant input 100-20Khz)
Recommended amp power	25-125 watt	(Recommended amp power to drive speaker)
Sensitivity	84.5 dB	Average SPL 2.83 Volt / 1mtr (on axis 200-10KHz)
System principle		In wall / Sealed enclosure
Connection	Terminal gold plating	Push terminals
Accessories	Yes	Cut out template / rear foam damping
Installation manual / guide		Yes
Mounting Depth	D	3.9 inch / 9.9 cm
Baffle dimensions	H x W	7.2 x 5.6 inch / 18.5 x 14.4 cm
Wall cut out	H x W	6.4 x 4.8 inch / 16.4 x 12.4 cm
Round Grill dimension	Diameter	9.2 inch / 23.5 cm
Square Grill dimension	H x W	8 x 6.4 inch / 20.5 x 16.4 cm
Weight		5.3 lbs/ 2,4kg
	Version 2. Juli 2011	