



## Specification Sheet

V15+		
Specifications / features.	Values / features	Notes / Comments.
THX® Certification	Yes	THX® Certification Class Ultra
Frequency Response	20-200 Hz	(Average Response in Room +/- 3 dB)
Frequency Roll Off	20 Hz	(-6 dB 16 Hz Nearfield )
Variable Low Pass Filter	42-300 Hz	App Controlled
Phase Control	0 - 360 deg	App Controlled
Line level input/output	2 x RCA phono	Left / Right - input / output
Amplifier type		Analog input / switch mode power output
Drive unit	1 x 15"	Long Throw
System Principle		Sealed enclosure
Amplifier Power output RMS	500 watt	<0.5% THD at 300W into 4 ohms
Amplifier Power output Peak	1000 watt	
Standby Power Consumption	0.8 watt	50W Average, 300W Max
Headroom Limiter Maximizer	Yes	(Dynamic driver excursion control)
Auto Power detect on/off	Yes	
Finish	Satin	Black
Dimensions	H x W x D	18.5 x 18.5 x 18.5 in / 470 x 470 x 470 mm
Weight	Netto	46.3 lbs / 30.7 kg
Manual	Yes	Safety Manual included in packing
Accessories	Yes	Gloves, US/EU Power cords, Rubber Feet
Version 1 - January 2022		

**The Choice of Professionals™**